

# Dark Premium Laser

## Application:

**Printer:** All color laser printers and color laser copiers, including Non-Oil Laser printers. Suitable for high resolution photographs.  
**Recommended Paper Mode:** Heavy Mode/ Thick Paper mode 2/ Label mode.

**Image:** Right Reading  
**Press Time:** 25-30 Seconds  
**Temperature:** 380-395°F (195-200°C)  
**Pressure:** Medium to Heavy  
**Peel:** Completely cool.

## Notes:

### Recommended Fabrics;

#### **All fabrics made of:**

Cotton  
Cotton blends  
Synthetic fabrics

#### Create your own:

T-shirts  
Caps  
Mouse pads  
Bags  
Can coolers etc.

#### Peeling:

Allow silicon to completely cool before peeling off.

#### Care Instruction:

Always turn textile inside out before washing. We recommend to machine wash in cold water. You may wash in warm water (40°C). Use a mild detergent and DO NOT USE any aggressive or bleaching agents. Recommend hang drying but can tumble dry with cool or warm air setting. DO NOT USE Fabric softeners. DO NOT dry clean. When ironing we recommend turning shirt insides out and ironing the image from the back.

### Step By Step:

**Step 1:** Feed transfer paper from bypass tray.

**Step 2:** Copy/Print on the coated, rough side of transfer paper.

**Step 3:** Copy/ Print **Right Reading, NOT mirror Image.**

**Step 4:** Copy/ Print in heavy mode/Thick Paper Mode 2/ Label mode.

**Step 5:** Pre-Press shirt for 5 seconds.

**Step 6:** Trim away the unprinted paper around your image with scissors.

**Step 7:** Remove transfer film from backing paper.

**Step 8:** Position imaged transfer film on garment with printed side face up.

**Step 9:** Cover imaged transfer film with enclosed silicon paper.

**Step 10:** Press at 380-395°F (195-200°C) using MEDIUM to HEAVY pressure for 25 seconds.

**Step 11:** Allow silicon to cool completely and peel off.

### HEAT TRANSFER WAREHOUSE

2201 12<sup>th</sup> St. N

Unit F

Fargo, ND 58102

Phone: 701-356-3160

Fax: 701-356-3162



[www.heattransferwarehouse.com](http://www.heattransferwarehouse.com)